



INDICATIVE PRODUCT IMAGE

## Product file

|              |               |
|--------------|---------------|
| Code         | BD1352MA60P12 |
| Gas          | R290          |
| Application  | MBP           |
| Series       | BD            |
| Expansion    | Valve         |
| Exchange     | Air           |
| Net weight   | 125 kg        |
| Gross weight | 165 kg        |
| Ped          | 0             |
| Noise        | 41.46 dBA 10m |
| Defrost      | Hot gas       |
| Mounting     | Wall          |
| Type         | Compact       |
| Version      | Swab          |

## Compressor

|                         |                          |
|-------------------------|--------------------------|
| Compressor no.          | 2                        |
| Compressor type         | Hermetic                 |
| Compressor brand        | EMBRACO                  |
| Compressor voltage      | 400/3/50                 |
| Compressor displacement | 2 x 27.8 cm <sup>3</sup> |

## Condenser

|                    |                        |
|--------------------|------------------------|
| Fan-motors no.     | 1                      |
| Fan blade diameter | 350 mm                 |
| Condenser air flow | 2700 m <sup>3</sup> /h |

## Evaporator

|                     |                        |
|---------------------|------------------------|
| Fan-motors no.      | 1                      |
| Fan blade diameter  | 350 mm                 |
| Air throw           | 8.00 m                 |
| Evaporator air flow | 2400 m <sup>3</sup> /h |

## Absorptions

|                           |          |
|---------------------------|----------|
| Power absorbed            | 2582 W   |
| Current absorbed          | 4.70 A   |
| Maximum current           | 11.60 A  |
| Machine electrical supply | 400/3/50 |

## Pipe fittings

|                     |       |
|---------------------|-------|
| Condensate drainage | 16 mm |
|---------------------|-------|

## Dimensions

|                  |         |
|------------------|---------|
| Width            | 915 mm  |
| Depth            | 1139 mm |
| Height           | 968 mm  |
| Width packaging  | 1020 mm |
| Depth packaging  | 1210 mm |
| Height packaging | 1150 mm |

## Refrigeration capacity table – BD1352MA60P12 – Refrigerant: R290

| Ambient temperature | Cell temperature | Cell volume           | Capacity |
|---------------------|------------------|-----------------------|----------|
| 25 °C               | -5 °C            | 52.40 m <sup>3</sup>  | 3869 W   |
| 25 °C               | 0 °C             | 76.10 m <sup>3</sup>  | 4452 W   |
| 25 °C               | 5 °C             | 112.00 m <sup>3</sup> | 5076 W   |
| 32 °C               | -5 °C            | 41.20 m <sup>3</sup>  | 3611 W   |
| 32 °C               | 0 °C             | 59.80 m <sup>3</sup>  | 4152 W   |
| 32 °C               | 5 °C             | 88.10 m <sup>3</sup>  | 4731 W   |
| 43 °C               | -5 °C            | 25.90 m <sup>3</sup>  | 3192 W   |
| 43 °C               | 0 °C             | 37.90 m <sup>3</sup>  | 3681 W   |
| 43 °C               | 5 °C             | 56.20 m <sup>3</sup>  | 4206 W   |

### Values referred to :

Suction gas : +20°C

Subcooling : 0K

Superheat : 100%



Compressor absorption :

*Te -5°C (HT); Tcond +50°C*

*Te -10°C (MT); Tcond +50°C*

*Te -30°C (LT); Tcond +50°C*

## Technical drawings – BD1352MA60P12





INDICATIVE PRODUCT IMAGE

- **Mechanical part main components**
  - Hermetic compressors with thermal motor protection
  - Condenser with Ø5mm tubes with internal spiral rifling
  - Evaporator with Ø5/16" tubes with internal spiral rifling
  - Electronic fan-motors on both condenser and evaporator
  - Mechanical thermostatic valve supplied standard across the entire range
  - Hot gas defrosting
  - Compressor crankcase heater
  - R290 refrigerant charge ≤ 150g per circuit
  - Condensation temperature control (ON/OFF fans for models size 10 + 30; Adjustable 0-10V fans for models size 40 + 60)
  - Condensing water direct discharge
  - Cold room light fixed on the panel under the evaporator
- **Control circuit and electrical part**
  - Safety pressure switch on high pressure side
  - High and low pressure probes
  - Power supply cable L= 2.5 m with wired electrical plug
  - Industrial Plug (2P+E or 3P+N+E) 16 A / 32A
- **ELECTRONIC CONTROL**
  - Rivolution: programmable electronic control with software developed by Rivacold
  - Safety Defrost function
- **STRUCTURE**
  - Self-bearing housing made of galvanized sheet which is coated with epoxy powder
  - Insulation plug for the cell hole included (thickness 100 mm)
- **OPTIONAL**
  - Catephoresis treatment of exchangers (Condenser + Evaporator)
  - Door micro switch with 10m long cable
  - Door heater cable (10m)
  - Accessory required for multiple units installed in the same cold room (1 per unit) – Master/Slave wiring kit (5 m cable)
  - Connection cable for BMS (RTU Modbus Protocol) L=5 m
  - Door resistance cable L = 10m
  - Electrical panel resistance (Ta < -10°C)
  - Remote control panel (10m)