



INDICATIVE PRODUCT IMAGE

Product file

Code	BD1352LA50P12
Gas	R290
Application	LBP
Series	BD
Expansion	Valve
Exchange	Air
Net weight	125 kg
Gross weight	165 kg
Ped	0
Noise	40.60 dBA 10m
Defrost	Hot gas
Mounting	Wall
Type	Compact
Version	Swab

Compressor

Compressor no.	2
Compressor type	Hermetic
Compressor brand	EMBRACO
Compressor voltage	400/3/50
Compressor displacement	2 x 33.42 cm ³

Condenser

Fan-motors no.	1
Fan blade diameter	350 mm
Condenser air flow	2700 m ³ /h

Evaporator

Fan-motors no.	1
Fan blade diameter	350 mm
Air throw	8.00 m
Evaporator air flow	2400 m ³ /h

Absorptions

Power absorbed	2160 W
Current absorbed	4.00 A
Maximum current	11.40 A
Machine electrical supply	400/3/50

Pipe fittings

Condensate drainage	16 mm
---------------------	-------

Dimensions

Width	915 mm
Depth	1139 mm
Height	968 mm
Width packaging	1020 mm
Depth packaging	1210 mm
Height packaging	1150 mm

Refrigeration capacity table – BD1352LA50P12 – Refrigerant: R290

Ambient temperature	Cell temperature	Cell volume	Capacity
25 °C	-25 °C	31.80 m ³	2241 W
25 °C	-20 °C	49.70 m ³	2660 W
25 °C	-15 °C	77.90 m ³	3111 W
32 °C	-25 °C	22.90 m ³	2072 W
32 °C	-20 °C	35.90 m ³	2460 W
32 °C	-15 °C	56.00 m ³	2885 W
43 °C	-25 °C	11.20 m ³	1800 W
43 °C	-20 °C	19.90 m ³	2149 W
43 °C	-15 °C	31.00 m ³	2526 W

Values referred to :

Suction gas : +20°C

Subcooling : 0K

Superheat : 100%



Compressor absorption :

Te -5°C (HT); Tcond +50°C

Te -10°C (MT); Tcond +50°C

Te -30°C (LT); Tcond +50°C

Technical drawings – BD1352LA50P12





INDICATIVE PRODUCT IMAGE

- **Mechanical part main components**
 - Hermetic compressors with thermal motor protection
 - Condenser with Ø5mm tubes with internal spiral rifling
 - Evaporator with Ø5/16" tubes with internal spiral rifling
 - Electronic fan-motors on both condenser and evaporator
 - Mechanical thermostatic valve supplied standard across the entire range
 - Hot gas defrosting
 - Compressor crankcase heater
 - R290 refrigerant charge ≤ 150g per circuit
 - Condensation temperature control (ON/OFF fans for models size 10 + 30; Adjustable 0-10V fans for models size 40 + 60)
 - Condensing water direct discharge
 - Cold room light fixed on the panel under the evaporator
- **Control circuit and electrical part**
 - Safety pressure switch on high pressure side
 - High and low pressure probes
 - Power supply cable L= 2.5 m with wired electrical plug
 - Industrial Plug (2P+E or 3P+N+E) 16 A / 32A
- **ELECTRONIC CONTROL**
 - Rivolution: programmable electronic control with software developed by Rivacold
 - Safety Defrost function
- **STRUCTURE**
 - Self-bearing housing made of galvanized sheet which is coated with epoxy powder
 - Insulation plug for the cell hole included (thickness 100 mm)
- **OPTIONAL**
 - Catephoresis treatment of exchangers (Condenser + Evaporator)
 - Door micro switch with 10m long cable
 - Door heater cable (10m)
 - Accessory required for multiple units installed in the same cold room (1 per unit) – Master/Slave wiring kit (5 m cable)
 - Connection cable for BMS (RTU Modbus Protocol) L=5 m
 - Door resistance cable L = 10m
 - Electrical panel resistance (Ta < -10°C)
 - Remote control panel (10m)